

SPECIFICATIONS

Product Description: **8" (20.3cm) METAL BLOWER, COM-PAX-IAL, AC**
 Part Number: **9534, 9534-15, 9534-25**
 Style: **AXIAL FAN, COMPACT**

GENERAL DESCRIPTION:

Lightweight and compact design allows for easy portability without sacrificing performance. Certified to CSA Standard C22.2 No.113.

CONSTRUCTION:

- Complete unit epoxy powder coated in "safety orange"
- 15-gauge cold rolled steel housing with welded motor mount construction
- 20-gauge steel canister
- Available with 15' (4.57m) or 25'(7.62m) ducting and canister
- Enclosed wide base for greater stability
- Steel/chrome plated grill
- Carry handle made of 3-ply rubber belting
- Equipped with four rubber feet

MOTOR:

HP: 1/3 HP
 Certifications: UL Recognized, CSA Certified
 Volts: 115V AC Single Phase
 RPM: 3200 (Loaded at 120 Volts, 60 Hz)
 Current Draw: 3.6A (Loaded at 120 Volts, 60 Hz)
 Cord: 6' (1.82 m) SJOOW 16/3 AWG neoprene, 300V medium duty
 Plug: NEMA 5-15 125V AC

DUCTING:

- Retractable, non-collapsible design
- Single ply, PVC coated, vinyl and polyester materials, temperature resistant up to 180° F (82.2° C)
- Yellow color with black weather-strip and integrated nylon straps
- Class 1 hard drawn spring steel wire helix that meets ASTM specs

FAN:

- Glass reinforced polypropylene (PPG) six blade fan with aluminum hub

BLOWER DIMENSIONS:

PN	Description	Length	Width	Height	Weight
9534	Blower only	12" (30.4 cm)	8" (20.3 cm)	10" (25.4 cm)	17 lbs. (7.7 kg)
9534-15	Blower w/ 15' Duct Canister	28" (71.1 cm)	11" (27.9 cm)	10" (25.4 cm)	34 lbs. (15.4 kg)
9534-25	Blower w/ 25' Duct Canister	28" (71.1 cm)	11" (27.9 cm)	10" (25.4 cm)	37 lbs. (16.7 kg)

FLOW RATES: (CFM calculated using 15' (4.57 m) of 8" (20.3 cm) ducting)

Free Air	One 90° Bend	Two 90° Bends
778 CFM (1231.83 m ³ /hr)	645 CFM (1095.86 m ³ /hr)	496 CFM (842.71 m ³ /hr)

