


NYLON SLINGS

HEAVY DUTY NYLON & POLYESTER SLINGS[†]

- 1) Heavy Duty Web thickness is approximately 3/16".
- 2) Eye length of Types 3 and 4 varies with sling width and number of webbing plies.



EYE LENGTH CHART

SLING WIDTH (IN)	PLIES OF WEBBING (IN)			
	1	2	3	4
1	8-1/2	8-1/2	10	10
2	10	10	12	12
3	11	11	14	14
4	12	12	16	16
5	14	14	18	18
6	16	16	18	18
8	20	20	24	24
10	24	24	24	24
12	24	24	24	24



ALL SLINGS ARE DOUBLE TAGGED FOR BETTER IDENTIFICATION

TYPES 1 & 2

WEB WIDTH (IN)	TYPE 1 (TC)	TYPE 2 (TT)	RATED CAPACITIES (LBS)			
			VERTICAL	CHOKER	BASKET	
1 PLY	2	TC1-802	TT1-802	3,200	2,400	6,400
	3	TC1-803	TT1-803	4,800	3,600	9,600
	4	TC1-804	TT1-804	6,400	4,800	12,800
	5	TC1-805	TT1-805	8,000	6,000	16,000
	6	TC1-806	TT1-806	9,600	7,200	19,200
	8	TC1-808	TT1-808	12,800	9,600	25,600
	10	TC1-810	TT1-810	16,000	12,000	32,000
	12	TC1-812	TT1-812	19,200	14,400	38,400
2 PLY	16	TC1-816	TT1-816	25,500	19,200	51,000
	18	TC1-818	TT1-818	28,700	21,000	57,400
	20	TC1-820	TT1-820	32,000	24,000	64,000
	24	TC1-824	TT1-824	38,400	28,800	76,800
	2	TC2-802	TT2-802	6,400	4,800	12,800
	3	TC2-803	TT2-803	8,600	6,500	17,200
	4	TC2-804	TT2-804	11,500	8,600	23,000
	5	TC2-805	TT2-805	14,000	10,500	28,000
3 PLY	6	TC2-806	TT2-806	16,800	12,600	33,600
	8	TC2-808	TT2-808	22,400	16,800	44,800
	10	TC2-810	TT2-810	28,000	21,000	56,000
	12	TC2-812	TT2-812	33,600	25,200	67,200
	16	TC2-816	TT2-816	44,800	33,600	89,600
	18	TC2-818	TT2-818	50,400	37,800	100,800
	20	TC2-820	TT2-820	56,000	42,000	112,000
	24	TC2-824	TT2-824	67,200	50,400	134,400

Three & Four Ply Hardware Slings are Available upon Request.
* Type Two cannot be used with a choker hitch.

† Monster-Edge available for all Heavy Duty Type Slings. Most web sling damage starts on the edge and progresses across the face of the webbing. Polymer coated yarns are woven into the edges of Monster-Edge sling webbing to reduce damage and increase its useful life.

Monster-Edge is 67% more resistant to edge cutting than standard sling webbing.

NOTE: Add an "M" onto the end of ordering code for Monster-Edge.

TYPES 3-FLAT EYE & 4-TWISTED EYE

WEB WIDTH (IN)	TYPE 5 (EE)	RATED CAPACITIES (LBS)			
		VERTICAL	CHOKER	BASKET	
1 PLY	1	EE1-801	1,600	1,200	3,200
	2	EE1-802	3,200	2,400	6,400
	3	EE1-803	4,800	3,600	9,600
	4	EE1-804	6,400	4,800	12,800
	5	EE1-805	8,000	6,000	16,000
	6	EE1-806	9,600	7,200	19,200
2 PLY	8	EE1-808	12,800	9,600	25,600
	10	EE1-810	16,000	12,000	32,000
	12	EE1-812	19,200	14,400	38,400
	1	EE2-801	3,200	2,400	6,400
	2	EE2-802	6,400	4,800	12,800
	3	EE2-803	8,600	6,500	17,200
3 PLY	4	EE2-804	11,500	8,600	23,000
	5	EE2-805	13,600	10,200	27,200
	6	EE2-806	16,300	12,200	32,600
	8	EE2-808	19,200	14,400	38,400
	10	EE2-810	22,400	16,800	44,800
	12	EE2-812	26,900	20,100	53,800
4 PLY	1	EE3-801	4,100	3,100	8,200
	2	EE3-802	8,300	6,200	16,600
	3	EE3-803	12,500	9,300	25,000
	4	EE3-804	16,000	12,000	32,000
	5	EE3-805	19,200	14,400	38,400
	6	EE3-806	23,000	17,200	46,000
5 PLY	8	EE3-808	30,700	23,000	61,400
	10	EE3-810	36,800	27,600	73,600
	12	EE3-812	44,000	33,000	88,000
	1	EE4-801	5,000	3,800	10,000
	2	EE4-802	10,000	7,500	20,000
	3	EE4-803	14,900	11,100	29,800
	4	EE4-804	19,800	14,800	39,600
	5	EE4-805	24,800	18,600	49,600
	6	EE4-806	29,800	22,300	59,600
	8	EE4-808	39,700	29,700	79,400
	10	EE4-810	49,600	37,200	99,200
	12	EE4-812	59,500	44,600	119,000

TYPE 5

WEB WIDTH (IN)	TYPE 5 (EE)	RATED CAPACITIES (LBS)			
		VERTICAL	CHOKER	BASKET	
1 PLY	1	EN1-801	3,200	2,500	6,400
	2	EN1-802	6,400	5,000	12,800
	3	EN1-803	8,600	6,900	17,200
	4	EN1-804	11,500	9,200	23,000
	5	EN1-805	13,600	10,900	27,200
	6	EN1-806	16,300	13,000	32,600
2 PLY	8	EN1-808	19,200	15,400	38,400
	10	EN1-810	22,400	17,900	44,800
	12	EN1-812	26,900	21,500	53,800
	1	EN2-801	6,200	4,900	12,400
	2	EN2-802	12,200	9,800	24,400
	3	EN2-803	16,300	13,000	32,600
3 PLY	4	EN2-804	20,700	16,500	41,400
	5	EN2-805	24,500	19,600	49,000
	6	EN2-806	28,600	23,000	57,200
	8	EN2-808	30,700	24,500	61,400
	10	EN2-810	33,600	26,800	67,200
	12	EN2-812	37,600	30,000	75,200
4 PLY	1	EN3-801	8,000	6,400	16,000
	2	EN3-802	16,000	12,800	32,000
	3	EN3-803	21,500	17,200	43,000
	4	EN3-804	28,700	23,000	57,400
	5	EN3-805	34,000	27,200	68,000
	6	EN3-806	40,700	32,500	81,400
5 PLY	8	EN3-808	46,000	36,800	92,000
	10	EN3-810	51,500	41,200	103,000
	12	EN3-812	59,200	47,300	118,400
	1	EN4-801	10,000	8,000	20,000
	2	EN4-802	19,800	15,800	39,600
	3	EN4-803	28,700	21,300	53,400
	4	EN4-804	35,600	28,400	71,200
	5	EN4-805	42,200	33,700	84,400
	6	EN4-806	50,500	40,400	101,000
	8	EN4-808	57,600	46,000	115,200
	10	EN4-810	67,200	53,700	134,400
	12	EN4-812	80,700	64,500	161,400

Tapering - Types 3, 4 & 5 are tapered at 3" & wider unless otherwise ordered. These wider slings are tapered at the bearing points to accommodate a crane hook.

Treatment - Unless specifically requested, all nylon web slings will have an abrasion resistant treatment applied. The standard for polyester web slings, however, is without treatment.

NOTE: Add a "P" to the end of Sling Code for Polyester. Polyester webbing is not available over 10" in width.

THE COST-EFFECTIVE CHOICE!

SINGLE PATH - ENDLESS POLYESTER ROUND SLINGS

- A flexible solution to your lifting needs.
- Rotation of lift points extends service life of sling.
- Length measure from Bearing Point to Bearing Point.
- Two same color polyester tubular jackets.
- The cost-effective choice!



ITEM NO.	COLOR	RATED CAPACITIES (LBS)			MIN. LENGTH (FT)	APPROX. MEASUREMENTS		
		VERTICAL	CHOKER	BASKET		WEIGHT (LBS/FT)	BODY DIA. RELAXED (IN)	WIDTH @ LOAD (IN)
SP260	Purple	2,600	2,100	5,200	1-1/2	.2	5/8	1-1/8
SP530	Green	5,300	4,200	10,600	1-1/2	.3	7/8	1-1/2
SP840	Yellow	8,400	6,700	16,800	3	.4	1-1/8	1-7/8
SP1060	Tan	10,600	8,500	21,200	3	.5	1-1/8	2-1/8
SP1320	Red	13,200	10,600	26,400	3	.7	1-3/8	2-1/4
SP1680	White	16,800	13,400	33,600	3	.8	1-3/8	2-1/2
SP2120	Blue	21,200	17,000	42,400	3	1.1	1-3/4	3
SP3100	Grey	31,000	24,800	62,000	3	1.6	2-1/4	3-3/4
SP5300	Brown	53,000	42,400	106,000	8	2.5	2-3/4	4-5/8
SP6600	Olive	66,000	52,800	132,000	8	3.1	3-1/8	5-1/4
SP9000	Black	90,000	72,000	180,000	8	4.0	3-5/8	6

NYLON SLINGS

REVERSED EYE (RE) SLINGS TYPE 6

Reversed Eye Sling is a modified endless sling. Cordura wear pads offer added protection on the body and eyes of the sling. This extra webbing offers superior abrasion resistance and sling life.


	CODE NO.	VERTICAL (LBS)	CHOKER (LBS)	BASKET (LBS)	SLING WIDTH (IN)	SLING THKNS. (IN)	EYE LENGTH (IN)
HEAVY DUTY WEB							
1 PLY	RE1-802	4,500	3,600	9,000	2	5/16	9
	RE1-804	7,700	6,200	15,400	4	5/16	15
	RE1-806	11,000	8,800	22,000	6	5/16	15
2 PLY	RE2-802	6,500	5,200	13,000	2	1/2	9
	RE2-804	13,000	10,400	26,000	4	1/2	15
	RE2-806	20,000	16,000	40,000	6	1/2	15
3 PLY	RE3-804	16,400	13,100	32,800	4	11/16	15
	RE3-806	25,500	20,400	51,000	6	11/16	15
4 PLY	RE4-806	34,000	27,200	68,000	6	7/8	15
LIGHT DUTY WEB							
1 PLY	RE1-602	3,600	2,900	7,200	2	1/4	9
	RE1-603-1/2	5,000	4,000	10,000	3-1/2	1/4	12
	RE1-604	6,800	5,400	13,600	4	1/4	15
	RE1-606	8,000	6,400	16,000	6	1/4	15
2 PLY	RE2-602	5,200	4,200	10,400	2	3/8	9
	RE2-603-1/2	9,000	7,200	18,000	3-1/2	3/8	12
	RE2-604	10,500	8,400	21,000	4	3/8	15
	RE2-606	14,400	11,500	28,800	6	3/8	15
3 PLY	RE3-603-1/2	12,000	9,600	24,000	3-1/2	1/2	12
	RE3-604	14,000	11,200	28,000	4	1/2	15
	RE3-606	20,000	16,000	40,000	6	1/2	15



CORDURA-WEB NYLON SLINGS

BEST IN ABRASION RESISTANCE

Available in two strength classes, all Cordura-Web slings feature abrasive resistant Cordurat yarns covering all surfaces, for extended sling life and long term value.



FEATURES, ADVANTAGES AND BENEFITS

- **Promotes Safety:** Red core yarn warning system aids in the inspection process, and striped webbing helps identify proper capacity.
- **Saves Money:** Abrasion resistant Cordura covering on faces and edges for greater sling life.
- **Saves Time:** Striped capacity for quick identification.

2000 Capacity Two Stripes = 2,000 lbs. per inch of width (one ply only). 25% stronger than other webbing. The strongest abrasion resistant sling available. Eyes of Cordura-Web 2000 slings for Types 3-4-5 are not tapered in any width.

1000 Capacity One Stripe = 1,000 lbs. per inch of width (one ply only). The only light duty web sling with Cordura surface. Wider bearing surface, per capacity, helps protect load surface. Cordura-Web slings meet or exceed DSHA & ASME B30.9 requirements. Eyes of one ply Cordura-Web 1000 slings are tapered for Types 3-4 in web widths 3 & 4 inches.

	BODY WIDTH (IN)	CODE	VERTICAL BASKET HITCH CAPACITY (LBS)	EYE LENGTH (IN)	EYE MAT'L. WIDTH (IN)	
CONTINUOUS EYE WIDE-LIFT						
1 PLY	6	WL1-806	15,400	9	1-1/2	Wide Lift (WL) Slings Continuous Eye Wide-Lift For Heavy Loads Constructed from one endless sling with the two body lengths butted and joined side by side. Stiffener webbing is used at the base of the eyes to deter the body webbing from folding down the middle.
	8	WL1-808	20,400	12	2	
	10	WL1-810	25,600	15	2-1/2	
	12	WL1-812	30,800	18	2	
	16	WL1-816	38,000	24	2-3/4	
	20	WL1-820	45,000	30	3-1/2	
2 PLY	6	WL2-806	28,600	9	1-1/2	Attached Eye Wide-Lift For Light, Bulky Loads that require wider bearing areas and some balance attributes. Eyes are made from separate material - WL A1 is 1 ply - WL A2 is 2 ply - both sewn to sling body. Body is single ply for both 1 and 2 ply eyes.
	8	WL2-808	38,000	12	2	
	12	WL2-812	57,200	18	3	
	16	WL2-816	75,000	24	4	
1 PLY EYE	6	WLA1-806	5,000	6	1	
	8	WLA1-808	5,000	8	1	
	10	WLA1-810	5,000	10	1	
	12	WLA1-812	5,000	12	1	
2 PLY EYE	6	WLA2-806	10,000	10	1	
	8	WLA2-808	10,000	10	1	
	10	WLA2-810	10,000	12	1	
	12	WLA2-812	10,000	12	1	
2 PLY EYE	16	WLA2-816	18,000	12	2	
	20	WLA2-820	18,000	16	2	
	24	WLA2-824	18,000	18	2	
	24	WLA2-824	18,000	18	2	

	CODE	WEB WIDTH (IN)	RATED CAPACITIES (LBS)			CODE	WEB WIDTH (IN)	RATED CAPACITIES (LBS)			
			VERTICAL	CHOKER	V BASKET			VERTICAL	CHOKER	V BASKET	
CORDURA-WEB 2000 CAPACITY						CORDURA-WEB 1000 CAPACITY					
TYPE U						TYPE U					
1 PLY	UU1-202	2	4,000	3,200	8,000	UU1-102	2	2,000	1,600	4,600	
	UU1-203	3	6,000	4,800	12,000	UU1-103	3	3,000	2,400	6,000	
	UU1-204	4	8,000	6,400	16,000	UU1-104	4	4,000	3,200	8,000	
2 PLY	UU2-202	2	8,000	6,400	16,000	UU2-102	2	4,000	3,200	8,000	
	UU2-203	3	10,800	8,600	21,600	UU2-103	3	5,400	4,300	10,800	
	UU2-204	4	14,400	11,500	28,800	UU2-104	4	7,200	5,700	14,400	
TYPE 3						TYPE 3					
1 PLY	EE1-201	1	2,000	1,600	4,000	EE1-101	1	1,000	800	2,000	
	EE1-202	2	4,000	3,200	8,000	EE1-102	2	2,000	1,600	4,000	
	EE1-203	3	6,000	4,800	12,000	EE1-103	3	3,000	2,400	6,000	
	EE1-204	4	8,000	6,400	16,000	EE1-104	4	4,000	3,200	8,000	
2 PLY	EE2-201	1	4,000	3,200	8,000	EE2-101	1	2,000	1,600	4,000	
	EE2-202	2	8,000	6,400	16,000	EE2-102	2	4,000	3,200	8,000	
	EE2-203	3	10,800	8,600	21,600	EE2-103	3	5,400	4,300	10,800	
	EE2-204	4	14,400	11,500	28,800	EE2-104	4	7,200	5,700	14,400	
TYPE 5						TYPE 5					
1 PLY	EN1-201	1	4,000	3,200	8,000	EN1-101	1	2,000	1,600	4,000	
	EN1-202	2	8,000	6,400	16,000	EN1-102	2	4,000	3,200	8,000	
	EN1-203	3	12,000	9,600	24,000	EN1-103	3	6,000	4,800	12,000	
	EN1-204	4	16,000	12,800	32,000	EN1-104	4	8,000	6,400	16,000	
2 PLY	EN2-201	1	7,800	6,200	15,600	EN2-101	1	3,900	3,100	7,800	
	EN2-202	2	15,200	12,200	30,400	EN2-102	2	7,600	6,100	15,200	
	EN2-203	3	20,400	16,300	40,800	EN2-103	3	10,200	8,200	20,400	
	EN2-204	4	25,800	20,600	51,600	EN2-104	4	12,900	10,300	25,800	

† Cordura is a registered trademark of DuPont.

ORDERING NYLON SLINGS

HOW TO ORDER: Sling Part No _____ Length _____ Type _____

EXAMPLE: Sling Part No **EE2-802** Length **10'** Type **3**

Eye-Eye 2 Ply Heavy Duty Nylon 2" Wide - 10' Length - Flat Eye

NOTE: Measurement of Length does not include the ring